



Introducing the new





The next generation of moisture meters is here, with the introduction of the Navigator[™] Series and *EDGE[™]* app from Delmhorst.





NEW CX-30

Delmhorst Instrument Co introduces the new model CX-30 cotton moisture meter. A high-quality moisture meter during harvest and ginning is an essential tool for measuring moisture content with confidence. Ensure a quality crop every time. The meter features the **EDGE**[™] app, to expand meter functionality and enabling users to save unlimited readings and share data from any location.

METER FEATURES

- Large, dashboard-like display easy to read under all conditions
- Rugged case design with E-Z grip handle and tactile switch array
- On-screen statistics High, Low, Average, Std Dev, View all
- Bluetooth[®] connectivity
- Calibrations for lint cotton, seed cotton, wool and viscose/rayon
- Alarm set point alerts to user-selected MC level
- Internal calibration check
- "Low Batt" warning with audio
- Auto-off timer set to 1m, 4m or 10m
- QR code on meter for easy access to support materials
- Compatible with any Delmhorst electrode
- Hard plastic carrying case included

METER SPECS

- Measuring ranges: Lint cotton (4%-18%), seed cotton (6%-20%), wool (12%-30%) and viscose/rayon (6%-25%).
- Display: Custom LCD with backlight, contrast and brightness settings
- Power: 2x AA Alkaline
- Op Temp: 0-255° F (-18-124°C)
- Size: 6in x 2.9in x1.6in (22cm x 7.4cm x 4.1cm)
- Weight: 6.9oz (20kg) without batteries; 8.6oz (24kg) with batteries
- 2-year warranty on manufacturer's defects bonus warranty with on-line registration

EDGE™ АРР

- Save unlimited readings
- Timestamp and geotag
- Data export to .csv file
- Customized LED ranges

CX-30 Electrodes



30-E/C - Used for bales - 9 1/2" insulated pins, with 8 1/4" penetration, eliminates the effect of surface moisture



52-E/C Cup - Used for lint or seed cotton





37-E/C - Used for yarn, 1 1/2" pins with 1" penetration



830-T/C – T-handle - Used for modules, heavy duty steel, 36"