

Introducing the new

# JLX-30

MOISTURE METER FOR LEATHER



The next generation of moisture meters is here, with the introduction of the **Navigator™** Series and **EDGE™** app from Delmhorst.

## NEW JLX-30

The JLX-30 leather moisture meter is a professional-grade, versatile and accurate device to address moisture issues in production, drying and quality control. The meter's rugged construction ensures years of reliability and is the ideal tool for leather applications and tanneries everywhere.

### Product Features

- Large, custom display with auto backlight – easy to read under all conditions
- Modern case design with large, tactile buttons and E-Z grip handle
- On-screen statistics – High, Low, Average, Standard Deviation, Last 10
- Moisture Range: 10%-28% MC Leather
- Temperature correction (°F/°C)
- Bluetooth® connectivity
- Color-coded LED's – adjustable through **EDGE™** app
- Alarm set point - alerts to user-selected MC level
- Internal calibration check
- "Low Batt" warning with audio
- Auto off timer. Set to 1 min, 4 min or 10 min
- Compatible with any Delmhorst external electrode

### Meter Specifications

- Power – 2x AA Alkaline batteries
- QR code on meter for easy access to support materials
- Size: meter only - 8.65in (220mm) x 2.85in (72mm) x 1.55in (39mm); in carry case - 9.5in (241mm) x 6.5in (165mm) x 2.5in (64mm)
- Weight: meter only - 0.4.5oz (1.3g); in carry case - 1.8oz (51g)
- Hard plastic carrying case – included
- 2-year warranty on manufacturer's defects. Bonus extended warranty with on-line registration.

### The Delmhorst **EDGE™** app offers:

- Timestamp and geotag
- Data export to .csv format
- Save unlimited readings
- Customized LED ranges
- Multi-language

---

## Optional Electrode Attachments



### 4-E – 4pin electrode

Fitted with four contact pins for 5/16" penetration (same as the integral pins on top of the meter) . Useful for the tough material and hard to reach spots. Standard pins are p/n 2497/A-100. Can also be fitted with 2497/A-103 uninsulated pins with 1 3/32" length and 11/16" penetration.



### 22-E - 2pin electrode

Fitted with two very sharp non-insulated contact pins for 7/16" penetration. (p/n A-111)